



Protape Alu R+

Technical data sheet

Description:

Protape Alu R+ is premium aluminum tape coated with an hot melt adhesive system using a siliconized paper release liner, features reinforcement with a denser mesh to provide extra strength and protection. The tape is supplied on a cardboard core.

PROTAPE ALU is specifically designed for use in HVAC systems for joining and sealing pipes, rolls, and insulation sheets. It is also suitable for applications in the ventilation industry for sealing and waterproofing protective metal linings.

Features:

Easy application: The tape features a self-adhesive surface for easy installation and secure bonding.

Superior durability: Very resistant and long-lasting.

Instructions for use: Remove the paper backing, taking care not to touch the adhesive surface.

Affix the tape firmly to the surface without stretching.

Surfaces to be joined must be clean, dry, and free of dust, grease, or oil.

Dimensions:

Custom sizes available upon request.

Standard dimensions include:

Thickness: 30 microns

Width: 50mm, 75mm, and 100mm

Length: 50m

PACKAGING PRESENTATION

Tapes: 50 mm x 50m

Box: 24 units.

Tapes: 75 mm x 50m

Box: 16 units.

Tapes: 100 mm x 50m

Box: 12 units.

Storage:

Store in a cool, dry place away from direct sunlight, at ambient temperature. Ensure that the product is kept in its original packaging and remains unopened until use.

Disclaimer:

The information provided in this technical data sheet is based on our current knowledge and experience. It is intended to be used as a guideline and does not constitute a warranty or guarantee. For any additional questions or uncertainties, we are at your disposal.